



# Movement Joints

for Industrial Flooring Contractors

Telephone +44 (0)1782 536719



## Technical Specifications For Movement Joints

### Movement Joints - DONMINI (UK) LTD

#### Movement Joints & Side Plates TG2 - (Tileguard 2)

TG2 - (Demarcation or perimeter applications). Suitable for use with ceramic floor tiles, marble and terrazzo tiles when fixing in adhesive bed.

Produced with 8mm wide polymeric seal insert, in black, cream or grey, other colours are available to order (subject to a minimum order quantity). 12mm wide available on request


Sideplates are available in stainless steel, brass and aluminium in standard thickness of 1.0mm. For heavy duty applications, sideplates of a greater thickness can be supplied. Standard lengths are 2 metres.

TG2 is also available with a **VAMAC** insert.


**VAMAC** has been tested and approved by London Underground Limited to meet their strict requirements for lox toxic fumes and fire resistance, under their 'Engineering Standard for the fire safety performance of materials used underground'



Product ref:	Side Plate Material	Heights	Visible width	Length
TG2	Aluminium, Stainless Steel or Brass	From 10mm upwards Contact for details	10mm	2 metres




**Movement Joints**  
Tileguard 1




**Movement Joints**  
Tileguard 2




**Movement Joints**  
Tileguard 3




**Movement Joints**  
Tileguard 4



**Tileguard Circles**



**Heavy Duty Angles**



**Technical Specification**



**Contact Donmini**  
sales@donmini.co.uk

FOR MORE INFORMATION TELEPHONE: +44 (0)1782 536719

© 2014 Donmini (UK) Limited - Movement Joints Registered in England

Registered Address: Unit 8/2 Norton Industrial Estate, Bellerton Lane, Norton, Stoke-on-Trent ST6 8ED United Kingdom

**IMPORTANT**

Whilst all reasonable care is taken in compiling technical data on the company's products, all recommendations or suggestions regarding the use of such products are made without guarantee since the conditions of use are beyond the company. It is the customers responsibility to satisfy himself that each product is fit for the purpose for which he intends to use it and that the actual conditions of use are suitable.