



Movement Joints

for Industrial Flooring Contractors

Telephone +44 (0)1782 536719



Technical Specifications For Movement Joints


Movement Joints - DONMINI (UK) LTD

Movement Joints & Sideplates Tileguard Circles

Standard size circles are available in Tileguard 3 (TG3), from 500mm dia upwards in increments of 250mm. A full curving service is also available on all products.


Produced with 8mm wide polymeric seal insert, in black, cream or grey, with 1mm side plates. 12mm wide available on request.

Tileguard Circles are also available with a **VAMAC** insert.



VAMAC has been tested and approved by London Underground Limited to meet their strict requirements for low toxic fumes and fire resistance, under their 'Engineering Standard for the fire safety performance of materials used underground'

Product ref:	Side Plate Material	Heights	Visible width	Length
TG Circles	Stainless Steel or Brass	From 25mm upwards Contact for details	10mm	2 metres




Movement Joints
Tileguard 1




Movement Joints
Tileguard 2




Movement Joints
Tileguard 3




Movement Joints
Tileguard 4



Tileguard Circles



Heavy Duty Angles



Technical Specification



Contact Donmini
sales@donmini.co.uk

FOR MORE INFORMATION TELEPHONE: +44 (0)1782 536719

© 2014 Donmini (UK) Limited - Movement Joints Registered in England

Registered Address: Unit 8/2 Norton Industrial Estate, Bellerton Lane, Norton, Stoke-on-Trent ST6 8ED United Kingdom

IMPORTANT
Whilst all reasonable care is taken in compiling technical data on the company's products, all recommendations or suggestions regarding the use of such products are made without guarantee since the conditions of use are beyond the company. It is the customers responsibility to satisfy himself that each product is fit for the purpose for which he intends to use it and that the actual conditions of use are suitable.